



# **AMS-02: TRDTN7 Octagon M-Structure**

**Author: Th. Kirn, Ch. Chung, K. Lübelmeyer, A. Schultz v. Dratzig  
I. Phys. Institute B, RWTH Aachen  
Aachen, 13th January 2009**


# TRD M-Structure Heating






Verwendungsbereich	Zul. Abw.	Oberfläche	Maßstab	Gewicht
		✓	Werkstoff. Halbzeug	
	2008	Datum	Benennung	
	Bearb.	25.11	M-Structure schematics	
	Gepr.		Thermostats & heaters	
	Name		Zeichnungsnummer	
			Blatt	
			3	
			AS Bl.	
Rev.	Änderung	Revision	Name	Ers. f.: Ers. d.: Plot Datum:






Verwendungsbereich	Zul. Abw.	Oberfläche	Maßstab	Gewicht
		Werkstoff, Halbzeug		
		Benennung		
		M-Structure schematics		
		Heaters		
		Zeichnungsnummer		Blatt
				2
		Bl.		
Rev.	Änderung	Revision Name	Ers. f.:	Ers. d.:
				Plot Datum:












**MS27508**  
**Rear, Box Mounting Receptacle**  
**AE208**



Bayonet Coupling, Crimp Removable, Rear Release, Low Profile/Light Weight

MIL-DTL-38999 S II



- Page 22 Completed Part Number
- Page 34 Contacts, Sealing Plugs and Tools
- Pages 17-19 Insert Arrangements
- Page 21 Performance Specifications
- Pages 15, 16 Insert Availability and Contact Information
- Page 32 Polarization


Note: See page 33 for panel thickness.

Shell Size	A		B		Ø C		Ø E		Ø F		Ø H	
	Maximum		(TP)		+0.01 -.005	+25 -13	±.003	±.08	Maximum		Maximum	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
8	.828	21.03	.594	15.09	.120	3.05	.471	11.96	.547	13.89	.299	7.59
10	.954	24.23	.719	18.26	.120	3.05	.588	14.94	.672	17.07	.427	10.85
12	1.047	26.59	.812	20.62	.120	3.05	.748	19.00	.844	21.44	.541	13.74
14	1.141	28.98	.906	23.01	.120	3.05	.873	22.17	.969	24.61	.666	16.92
16	1.234	31.34	.969	24.61	.120	3.05	.998	25.35	1.094	27.79	.791	20.09
18	1.328	33.73	1.062	26.97	.120	3.05	1.123	28.52	1.219	30.96	.897	22.78
20	1.453	36.91	1.156	29.36	.120	3.05	1.248	31.70	1.344	34.14	1.022	25.96
22	1.578	40.08	1.250	31.75	.120	3.05	1.373	34.87	1.469	37.31	1.147	29.13
24	1.703	43.26	1.375	34.93	.147	3.73	1.498	38.05	1.594	40.49	1.272	32.31


www.conesys.com


- 26 -


sales@aero-electric.com














# TRD M-Structure Heating Space Qualification

# TRD M-Structure Heating Thermostat Box #2

**Space Qualification**  
**TRD Heating Thermostat Box 02–**  
**Vibration Test & Thermal Vacuum Test**

St Schmitz, 11.11.2008

Thermostat Box 02 has been qualified via Vibration-Test (VT).

VT (30.05.2008): Thermostat Box 02

- Random vibration in 3-dimensions (x, y, z)
- Acceleration Level = 6.8gRMS

Control Channel - Profile Settings

	Status	Frequency [Hz]	G <sup>2</sup> /Hz	Slope (dB/okt)	-Alarm (dB)	+Alarm (dB)	-Abort (dB)	+Abort (dB)
1	On			3.0	12.0	12.0	24.0	24.0
2	On	80.0	0.0400000		12.0	12.0	24.0	24.0
3	On	500.0	0.0400000		12.0	12.0	24.0	24.0
4	On			-3.0	12.0	12.0	24.0	24.0

I<sup>st</sup> Physics Institute B

Vibration setup x-axis:



Fig. 1 Thermostat Box 02 mounted on Vibration-table in x-axis








Fig. 2 Thermostat Box 02 mounted on Vibration-table in x-axis; top view





Vibration setup y-axis:








Fig. 3 ThermoStat Box 02 mounted on Vibration-table in y-axis



Fig. 4 ThermoStat Box 02 mounted on Vibration-table in y-axis





Vibration setup z-axis:




Fig. 5 Thermostat Box 02 mounted on Vibration-table in z-axis








Fig. 6 Thermostat Box 02 mounted on Vibration-table in z-axis



Thermostat Box 02 has been qualified via one Thermal-Vacuum-Test (TVT).

TVT (04.06.2008): Thermostat Box 02

- Switching Points of the four Thermostats
- 5 cycles from  $-25^{\circ}\text{C}$  to  $45^{\circ}\text{C}$
- Voltage  $\sim 110\text{V}$

TVT setup layout:




Fig. 7 TVT setup Thermostat Box 02 Power Supply, Thermostats, Voltmeter & Resistor

Voltage is measured with a Keithley Multimeter (Typ 2701) before and behind the resistor ( $R=3300\Omega$ ). Temperature Sensors T1 & T2 (PT1000) was mounted on the cover of Thermostat Box 02.

Thermostat switching points:

- |            |                                   |                                  |
|------------|-----------------------------------|----------------------------------|
| No. 00104: | On at $T=11.54^{\circ}\text{C}$ , | Off at $T=18.84^{\circ}\text{C}$ |
| No. 00120: | On at $T=9.65^{\circ}\text{C}$ ,  | Off at $T=19.70^{\circ}\text{C}$ |
| No. 00092: | On at $T=11.80^{\circ}\text{C}$ , | Off at $T=19.37^{\circ}\text{C}$ |
| No. 00097: | On at $T=10.00^{\circ}\text{C}$ , | Off at $T=18.19^{\circ}\text{C}$ |

Mean value of the five cycles.




Fig. 8 Environment, Temperature sensor T1 & T2 on Thermostat Box 02




Fig. 9 Switching Points of the Thermostats




Fig. 10 TVT Environment

PT = pressure in tank

TC = temperature on copper plate

T BP = temperature on base plate of Box 02

T SSP = temperature on sandwich support plate (honeycomb)






Fig. 11 Thermostat Box 02 on copper plate inside TVT, TC=T copper plate




Fig. 12 Thermostat Box 02, Position of the Thermostats




Fig. 13 Thermostat Box 02, detail sandwich support plate (honeycomb)

T1 = temperature on side of Box 02

T2 = temperature on base plate of Box 02

T BP = temperature on base plate of Box 02

T SSP = temperature on sandwich support plate (honeycomb)




Fig. 14 Temperature sensor T BP, T SSP, T1 & T2

# TRD M-Structure Heating Thermostat Box #4



# Space Qualification

## TRD Heating Thermostat Box 04

### Vibration Test & Thermal Vacuum Test

St Schmitz, 04.07.2008

Thermostat Box 04 has been qualified via Vibration-Test (VT).

VT (03.07.2008): Thermostat Box 04

- Random vibration in 3-dimensions (x, y, z)
- Acceleration Level = 6.8gRMS

Control Channel - Profile Settings

	Status	Frequency [Hz]	G <sup>2</sup> /Hz	Slope (dB/okt)	-Alarm (dB)	+Alarm (dB)	-Abort (dB)	+Abort (dB)
1	On			3.0	12.0	12.0	24.0	24.0
2	On	80.0	0.0400000		12.0	12.0	24.0	24.0
3	On	500.0	0.0400000		12.0	12.0	24.0	24.0
4	On			-3.0	12.0	12.0	24.0	24.0

Vibration setup x-axis:








Fig. 1 Thermostat Box 04 mounted on Vibration-table in x-axis



Vibration setup y-axis:








Fig. 2 Thermostat Box 04 mounted on Vibration-table in y-axis





Vibration setup z-axis:








Fig. 3 Thermostat Box 04 mounted on Vibration-table in z-axis



Thermostat Box 04 has been qualified via one Thermal-Vacuum-Test (TVT).

TVT (04.07.2008): Thermostat Box 04

- Switching Points of the four Thermostats
- 5 cycles from  $-25^{\circ}\text{C}$  to  $45^{\circ}\text{C}$
- Voltage  $\sim 110\text{V}$

TVT setup layout:




Fig. 4 TVT setup Thermostat Box 04 Power Supply, Thermostats, Voltmeter & Resistor

Voltage is measured with a Keithley Multimeter (Typ 2701) before and behind the resistor ( $R=3300\Omega$ ). Temperature Sensors T1 & T2 (PT1000) was mounted on the cover of Thermostat Box 04.

Thermostat switching points:

No. 00090:	On at $T=10.22^{\circ}\text{C}$ ,	Off at $T=17.99^{\circ}\text{C}$
No. 00086:	On at $T=10.59^{\circ}\text{C}$ ,	Off at $T=18.83^{\circ}\text{C}$
No. 00092:	On at $T=10.06^{\circ}\text{C}$ ,	Off at $T=18.87^{\circ}\text{C}$
No. 00097:	On at $T=9.71^{\circ}\text{C}$ ,	Off at $T=17.86^{\circ}\text{C}$

Mean value of the five cycles.




Fig. 5 Environment, Temperature sensor T2 on Thermostat Box 04




Fig. 6 Switching Points of the Thermostats






Fig. 8 Thermostat Box 04 on copper plate inside TVT, TC=T copper plate




Fig. 9 Thermostat Box 04, Position of the Thermostats

# TRD M-Structure Heating Thermostat Box #6



# Space Qualification

## TRD Heating Thermostat Box 06

### Vibration Test & Thermal Vacuum Test

St Schmitz, 10.07.2008

Thermostat Box 06 has been qualified via Vibration-Test (VT).

VT (03.07.2008): Thermostat Box 06

- Random vibration in 3-dimensions (x, y, z)
- Acceleration Level = 6.8gRMS

Control Channel - Profile Settings

	Status	Frequency [Hz]	G <sup>2</sup> /Hz	Slope (dB/okt)	-Alarm (dB)	+Alarm (dB)	-Abort (dB)	+Abort (dB)
1	On			3.0	12.0	12.0	24.0	24.0
2	On	80.0	0.0400000		12.0	12.0	24.0	24.0
3	On	500.0	0.0400000		12.0	12.0	24.0	24.0
4	On			-3.0	12.0	12.0	24.0	24.0

Vibration setup x-axis:








Fig. 1 Thermostat Box 06 mounted on Vibration-table in x-axis



Vibration setup y-axis:








Fig. 2 Thermostat Box 06 mounted on Vibration-table in y-axis





Vibration setup z-axis:








Fig. 3 Thermostat Box 06 mounted on Vibration-table in z-axis





Thermostat Box 06 has been qualified via one Thermal-Vacuum-Test (TVT).

TVT (07.07.2008): Thermostat Box 06

- Switching Points of the four Thermostats
- 5 cycles from -25°C to 45°C
- Voltage ~110V

TVT setup layout:




Fig. 4 TVT setup Thermostat Box 06 Power Supply, Thermostats, Voltmeter & Resistor

Voltage is measured with a Keithley Multimeter (Typ 2701) before and behind the resistor ( $R=3300\Omega$ ). Temperature Sensors T1 & T2 (PT1000) was mounted on the cover of Thermostat Box 06.

Thermostat switching points:

No. 00103:	On at $T=9.27^{\circ}\text{C}$ ,	Off at $T=19.07^{\circ}\text{C}$
No. 00108:	On at $T=11.14^{\circ}\text{C}$ ,	Off at $T=18.93^{\circ}\text{C}$
No. 00100:	On at $T=10.48^{\circ}\text{C}$ ,	Off at $T=18.25^{\circ}\text{C}$
No. 00107:	On at $T=10.67^{\circ}\text{C}$ ,	Off at $T=19.14^{\circ}\text{C}$

Mean value of the five cycles.




Fig. 5 Environment, Temperature sensor T2 on Thermostat Box 06




Fig. 6 Switching Points of the Thermostats




Fig. 7 Thermostat Box 06 on copper plate inside TVT, TC=T copper plate




Fig. 8 Thermostat Box 06, Position of the Thermostats

# TRD M-Structure Heating Thermostat Box #8

# Space Qualification

## TRD Heating Thermostat Box 08

### Vibration Test & Thermal Vacuum Test

St Schmitz, 14.07.2008

Thermostat Box 08 has been qualified via Vibration-Test (VT).

VT (03.07.2008): Thermostat Box 08

- Random vibration in 3-dimensions (x, y, z)
- Acceleration Level = 6.8gRMS

Control Channel - Profile Settings

	Status	Frequency [Hz]	G <sup>2</sup> /Hz	Slope (dB/okt)	-Alarm (dB)	+Alarm (dB)	-Abort (dB)	+Abort (dB)
1	On			3.0	12.0	12.0	24.0	24.0
2	On	80.0	0.0400000		12.0	12.0	24.0	24.0
3	On	500.0	0.0400000		12.0	12.0	24.0	24.0
4	On			-3.0	12.0	12.0	24.0	24.0

Vibration setup x-axis:








Fig. 1 Thermostat Box 08 mounted on Vibration-table in x-axis







Vibration setup y-axis:








Fig. 2 Thermostat Box 08 mounted on Vibration-table in y-axis



Vibration setup z-axis:








Fig. 3 Thermostat Box 08 mounted on Vibration-table in z-axis





Thermostat Box 08 has been qualified via one Thermal-Vacuum-Test (TVT).

TVT (09.07.2008): Thermostat Box 08

- Switching Points of the four Thermostats
- 5 cycles from  $-25^{\circ}\text{C}$  to  $45^{\circ}\text{C}$
- Voltage  $\sim 110\text{V}$

TVT setup layout:




Fig. 4 TVT setup Thermostat Box 08 Power Supply, Thermostats, Voltmeter & Resistor

Voltage is measured with a Keithley Multimeter (Typ 2701) before and behind the resistor ( $R=3300\Omega$ ). Temperature Sensors T1 & T2 (PT1000) was mounted on the cover of Thermostat Box 08.

Thermostat switching points:

No. 00113:	On at $T=10.78^{\circ}\text{C}$ ,	Off at $T=18.46^{\circ}\text{C}$
No. 00119:	On at $T=11.11^{\circ}\text{C}$ ,	Off at $T=18.3^{\circ}\text{C}$
No. 00110:	On at $T=11.6^{\circ}\text{C}$ ,	Off at $T=18.07^{\circ}\text{C}$
No. 00115:	On at $T=11.2^{\circ}\text{C}$ ,	Off at $T=18.71^{\circ}\text{C}$

Mean value of the five cycles.




Fig. 5 Environment, Temperature sensor T2 on Thermostat Box 08




Fig. 6 Switching Points of the Thermostats




Fig. 7 Thermostat Box 08 on copper plate inside TVT, TC=T copper plate




Fig. 8 Thermostat Box 08, Position of the Thermostats